

Mira Evoco

Mixer Shower



SUITABLE FOR ALL SYSTEMS



5 YEAR WARRANTY

Beauty, built-in.
Contemporary mixer
shower - designed
for style, ease of use
and reliability.

Product Information

Description	Colour	Product No.
Mira Evoco Single Outlet Shower	Chrome	1.1967.051
Mira Evoco Single Outlet Valve Only	Chrome	1.1967.079

Features & Benefits

Temperature control

Thermostatic temperature stability

Easy to fit

Mira's innovative installation system, providing a simple first fix solution

Flushing system provided to test connections prior to tiling

Suitable for rear wall installations

For your customer

Works on all systems, even at low pressure

Maximum temperature stop for increased safety (with override for a hotter shower)

Mira Cool Shield™ to ensure valve doesn't get hot during showering

One spray 11cm showerhead with rub-clean nozzles

1.25m flexible shower hose



Product Specification

Tech Details

Temperature and flow control

Temperature control type: Thermostatic

Flow actuation: Single sequential cartridge

Installation

Water entry points: Side only

Inlet connections: Compression fittings

Outlet connections: 15mm copper pipework

Reversed inlets supported: Yes

Supply Conditions (hot and cold)

Cold water range: 1°C to 25°C

Hot water range: Min 55°C; 60°C - 65°C (recommended)

Minimum maintained pressure (gas water heater) :
1 bar (10 metre head)

Minimum maintained pressure (gravity system) : 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

Performance

Flow rate (at handset): 9.75 l/min at 0.5 bar

Flow regulator: 6 l/min (supplied with product - x1)

Temperature stability: $\pm 2^\circ\text{C}$

Safety Features

Automatic shutdown: Shutdown within 2 secs

Factory set to safe maximum temperature

Adjustable maximum temperature for on-site conditions

Approvals

KIWA UK approved product

WRAS approved (Water Regulations Advisory Scheme)

TMV2 approved product

CE approved product

UKCA approved product



Dimensions

